


NOTES:  
 1.MATERIAL:  
 BODY:HI-TEMP. PLASTIC,BLACK,UL 94V-0  
 TERMINAL:COPPER ALLOY,T=0.10mm  
 SHELL:STAINLESS STEEL,T=0.15mm  
 2.FINISH:  
 TERMINAL:50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON CONTACT AREA  
 60-200u" MATTE TIN PLATED ON SOLDER TAIL AREA  
 SHELL:50u" Ni MIN UNDER PLATING OVER ALL  
 60-200u" TIN PLATED ON SOLDER TAIL AREA  
 3.ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: B38-AB03F15D
				DATE: 10/07/2013	X. ±0.20 .X ±0.15 .XX ±0.10 .XXX ±0.05	X° ±2.00° .X° ±1.00° .XX° ±0.50° .XXX° ±0.10°	CHECKED:	TITLE: 1.5H 测压式的Battery
B	E1403045A	端子锡脚电镀由亮锡->雾锡	03/10/2014	SCALE: 10:1			APPROVE:	DRAWING NO:
A		NEW	10/07/2013	SHEET: 1/1	MATERIAL:		 <b>鸿日达电子科技有限公司</b> HONGRIDA ELECTRONIC TECHNOLOGY CO.,LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. B	FINISH: SEE NOTE			