



RECOMMENDED PCB LAOUT
TOLERANCE(.XX±0.05)

NOTES:

1. MATERIAL:
 BODY:HI-TEMP. PLASTIC, BLACK, UL 94V-0
 TERMINAL:COPPER ALLOY, T=0.20mm
 SHELL:STAINLESS STEEL T=0.15mm
2. FINISH:
 TERMINA:
 40u" Ni MIN UNDER PLATING OVER ALL
 AU 2u" MIN ON CONTACT AREA
 60-200u" TIN PLATED ON SOLDER AREA
 SHELL:
 50u" Ni MIN UNDER PLATING OVER ALL
 GOLD FLASH AU ON SOLDER AREA
3. ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
4. RESISTANCE TO CURRENT: 3A MAX

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
				DATE: 05/16/2018	X. ±0.20	X.° ±2.00°	CHECKED:	B50-AB04F10B
				SCALE: 8 / 1	.X ±0.15	.X° ±1.00°	APPROVE:	NAME: 4PIN 2.50 PITCH BATTERY CONN.
					.XX ±0.10	.XX° ±0.50°		DRAWING NO: C-B50-0000_A
				SHEET: 1 / 1	.XXX ±0.05			
A		NEW	05/16/2018	REV. A	TITLE: CUSTOMER DRAWING		昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO.,LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	FINISH: SEE NOTE				