



RECOMMENDED PCB LAYOUT TOLERANCE (.XX ± 0.05)

- NOTES:
- MATERIAL:  
 BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0  
 TERMINAL: COPPER ALLOY, T=0.10mm  
 SHELL: STAINLESS STEEL T=0.15mm
  - GP PASSED ACCORD WITH HRD-ROHS-219 STANDARD.
  - FINISH:  
 TERMINA:  
 50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON CONTACT AREA  
 60-200u" TIN PLATED ON SOLDER AREA  
 SHELL:  
 50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON SOLDER AREA
  - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC  
 ALL DIMENSIONS MARKER (XX) MUST BE MEASURE BY FAI.

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: B62-AA04F10A
				DATE: 07/27/2016	X. ±0.20 .X ±0.15	X.° ±2.00° .X° ±1.00°	CHECKED:	TITLE: 4PIN 2.50 PITCH BATTERY CONN.
				SCALE: 8 / 1	.XX ±0.10 .XXX ±0.05	.XX° ±0.50°	APPROVE:	DRAWING NO:
A		NEW	07/27/2016	SHEET: 1 / 1	MATERIAL:		昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO.,LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE			