



T-CARD PIN NO.	PIN NO.
T1	DAT2
T2	CD/DAT3
T3	CMD
T4	VDD
T5	CLK
T6	VSS
T7	DAT0
T8	DAT1
SIM CARD PIN NO.	PIN NO.
P1-A/B	VCC
P2-A/B	RST
P3-A/B	CLK
P5-A/B	GND
P6-A/B	VPP
P7-A/B	I/O

NOTES:
 1. MATERIAL:
 HOUSING:LCP, BLACK, UL 94V-0
 CONTACT:PHOSPHOR BRONZE, T=0.12MM
 SHELL:STAINLESS STEEL T=0.20MM
 2. FININSH
 CONTACT: 50U'' MIN PLATING OVER ALL
 GOLD FLASH ON THE CONTACT AREA AND SOLDER AREA
 SHELL:SELECTIVE GOLD FLASH IN SOLDER TAIL AREA
 50U'' NI MIN. PLATING OVER ALL
 3. GP PASSED ACCORD WITH HRD-RoHS-219 STANDARD.
 4. ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 5. ALL DIMENSIONS MARKER (XX) MUST BE MEASURE BY FAI.

UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: S110-2B20F45A
DATE: 03/04'2017	X. ±0.25	X° ±5.00°	CHECKED:	TITLE: SIM CARD + SIM CARD + T-CARD 全插脚总高 4.50H 底部避空1.78H
SCALE: 4 / 1	.X ±0.15	.X° ±3.00°	APPROVE:	DRAWING NO:
SHEET: 1 / 1	.XX ±0.10	.XX° ±1.00°	MATERIAL:	
REV. A	.XXX ±0.05	.XXX° ±0.50°	FINISH: SEE NOTE	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A

RECOMMENDED PCB LAYOUT
 GENERAY TOLERANCE ± 0.05

